Type		Desktop		RackMount				
Model		NAS-1401	NAS-1400	NAS-5401	NAS-5402	NAS-6401	NAS-9402	NAS12-38800
Hardware								
Hardware	Processor	Intel® EP80579 1.2Ghz	Intel® EP80579 1.2Ghz	Intel Quad-core Xeon 3 GHz	Intel Quad-core Xeon 3 GHz	2 Intel Nehalem Processors 2.26Ghz	2 Intel Nehalem Processors 2.26Ghz	Intel Quad Core Xeon Processors Intel Blackford 5000P 3Ghz
	Memory	512	1Gb	1Gb	1Gb	1Gb	1Gb	2Gb
	Interface	Ethernet: 3x10/100/1000Mbps Console: RJ45 USB 2.0: 2	Ethernet: 3x10/100/1000Mbps Console: RJ45 USB 2.0: 2	Ethernet:12x10/100/1000Mbp Console: RJ45 USB 2.0: 2	Ethernet: 8x10/100/1000Mbps + 2xSFP Console: RJ45 USB 2.0: 2	Ethernet: 24x10/100/1000Mbps Console: RJ45 USB 2.0: 2	Ethernet:16x10/100/1000Mbps + 4xSFP Console: RJ45 USB 2.0: 2	Ethernet: 8x10/100/1000Mbps + 4xSFP Console: RJ45 USB 2.0: 2
	Reset button	x	x	x	x	x	x	x
	Power	AC 115 ~ 230V / 50 ~ 60 Hz 220W	AC 115 ~ 230V / 50 ~ 60 Hz 220W	AC 90 ~ 264V 600W (Redundant)	AC 90 ~ 264V 600W (Redundant)	AC 90~264 500W (redundant)	AC 90~264 500W (redundant)	AC 90~264 910W (reduntdant)
	Dimension	160 x 214 x 235 mm	161 x 214 x 235 mm	426x88.8x584 mm	426x88.8x584 mm	442x88x660 mm	442x88x660 mm	610x 442 x 130mm
	Weight	4.5kg	4.5kg	20kg	20kg	22kg	22kg	38kg
Enviroments	Temperature	Operating: 0ºC to 40ºC (32 to 104℉)	Operating: 0ºC to 40ºC (32 to 104℉)	Operating: 0ºC to 40ºC (32 to 104℉)	Operating: 0ºC to 40ºC (32 to 104℉)	Operating: 0ºC to 40ºC (32 to 104℉)	Operating: 0ºC to 40ºC (32 to 104℉)	Operating: 0ºC to 40ºC (32 to 104℉)
	Humidity	Storage: -20ºC to 55ºC (-4 to 67℉)	Storage: -20ºC to 55ºC (-4 to 67℉)	Storage: -20ºC to 55ºC (-4 to 67℉)	Storage: -20ºC to 55ºC (-4 to 67℉)	Storage: -20ºC to 55ºC (-4 to 67℉)	Storage: -20ºC to 55ºC (-4 to 67℉)	Storage: -20ºC to 55ºC (-4 to 67℉)
Features								
Network Protocol Support	Standards	IEEE 802.3, IEEE 802.3ab, IEEE 802.3u						
	Protocol Support	Samba, Netatalk, NFS, FTP						
	Advance Protocols	TFTP, SCP, iSCSI, RSYNCE, Unision						
	Services support	Transmission BitTorrent client, UPnP, Firefly iTunes						
	Client OS	Windows, Linux/Unix, Mac OS						
RAID Systen	Drive bays	4 x 3.5”						
	Drive Interface	SATA II 3.0Gbps						
	Max capacity	4TB						
	Raid Levels	0, 1, 10 and 5						
	Hot Swap	Yes						
Extra Services	Firewall	SPI Firewall						
	Authenticate	On-demand account, domain user						
	Network	802.1q VLAN, Wireless, Wake on LAN Link Aggregation						
	Management	Web, SNMP, System log, Email Alert						
Performance								
Max User Account		64	32	128	128	256	256	512
Max concurrent Users		16	16	64	64	64	64	64
Shared Folder		1024	1024	1024	1024	1024	1024	4096